

BARO

GmbH



VOLTYRE
PROM

BARO GmbH
REIFEN für Landwirtschaft - LKW - PKW



LIGHT TRUCK TIRES VOLTYRE





Tire size, Model:

185/75R16C VOLTYRE VS-22

For «Gazelle» cars and their analogues with tires of the same dimension, considering restrictions for speed and load characteristics.



Tire size, Model:

185/75R16C VOLTYRE VL-54

For «Gazelle», «Sobol» cars and their modifications as well as other cars of the same class with the appropriate speed and load characteristics.

GIMBEH

Tire size, model	TL/TT	Load index and speed symbol	Max speed, km/h	Max load, kg	Inflation pressure, kPa	Overall diameter, mm	Section width*, mm	Static loaded radius, mm	Rim contour designation (recommended/ approved)	Tube designation	Valve designation	Flap designation	Ply Rating	Weight, not more, kg
185/75R16C VOLTYRE VS-22	TT	104N* 102N**	140	900* 850**	470	684±7	184	316±3	5Jx16/ 5½Jx16, 6Jx16	UK-16-1 (6.95-16- permitted)	LK-35- 11,7	-	-	13,5
185/75R16C VOLTYRE VL-54	TT	104Q* 102Q**	160	900* 850**	470	684±7	184	316±3	5Jx16/ 5½Jx16, 6Jx16	UK-16-1	LK-35- 11,7	-	-	13,0

*The load and load index are indicated for single wheels.

** The load and load index are indicated for dual wheels.

***Cross section width is indicated for the rim 5 1/2Jx16

NOTE: The inflation pressure in the tire is always determined by the load on the tire, speed and type of work performed.



Tire size, Model:

185/75R16C VOLTYRE C-156

For «Gazelle», «Sobol» cars and import analogues considering the restrictions for speed and load characteristics.



Tire size, Model:

7,50-16C VOLTYRE BRI-317

Ply rating 12 is for use on light trucks and buses of small capacity considering the restrictions for the speed and load characteristics. Ply rating 10 is for use on vans: van AVIA-A21F, AVIA-A20L.

Tire size, model	TL/TT	Load index and speed symbol	Max speed, km/h	Max load, kg	Inflation pressure, kPa	Overall diameter, mm	Section width*, mm	Static loaded radius, mm	Rim contour designation (recommended/ approved)	Tube designation	Valve designation	Flap designation	Ply Rating	Weight, not more, kg
185/75R16C VOLTYRE C-156	TT	104Q* 102Q**	160	900* 850**	470	684±7	184	316±3	5Jx16/ 5½Jx16, 6Jx16	UK-16-1	LK-35-11,7	-	-	12,8
7,50-16C VOLTYRE BRI-317	TT	116L	120	1250	466	806±12	220	380±6	6J/ 6L	6,00-16	LK-35-16,5	-	10	24
		120L* 116L**		1405* 1240**	620	810±12		382±6	6,00/ 6J				12	26

*The load and load index are indicated for single wheels.

** The load and load index are indicated for dual wheels.

*** Cross section width is indicated for the rim 5 1/2Jx16.

NOTE: The inflation pressure in the tire is always determined by the load on the tire, speed and type of work performed..