

INTERNATIONAL STRATEGY



In order to promote its high-quality global industrial layout and increase its core brand competitiveness in global market, Linglong formulates its 6+6 global layout to build six Chinese manufacturing bases as well as six overseas manufacturing bases. At present, the company has five Chinese manufacturing bases in Zhaoyuan, Dezhou, Liuzhou, Jingmen, Changchun (under construction) and two overseas manufacturing bases in Thailand and Serbia (under construction). Meanwhile, Linglong will carry out active inspection of its new factory's location, aiming at completing the full completion of 6+6 global layout, and fully utilizing global resources and expanding its global tire market.



OFFIZIELLER VERTRIEBSPARTNER IN DEUTSCHLAND

+49 (40) 219 0 129-0 Melden Sie sich telefonisch bei uns, wir beraten Sie gerne.

> BaRo GmbH Hans-Duncker-Straße 9 21035 Hamburg

info@baro-reifen.de www.baro-reifen.de www.shop.baro-reifen.de

Agricultural Tire Tractors



LR861 Radial Agricultural Tire

- 1. Better traction and braking performance.
- 2. Save work time and fuel.
- 3. Better running stability.
- 4. Suitable for modern mechanical equipment.

Size	Load	Speed	Rim	Max.Load	Inflated Pressure	Overall Diameter	Section Width	Tread Depth			F	Press	ure(l	кРа)-	Load	per	tyre	in kg			
3120	Index	Symbols	14111	(kg)	(kPa)	(mm)	(mm)	(mm)	kPa	60	80	100	120	140	160	200	240	280	320	360	400
280/85R24	115/112	A8/B	W9W10	1215	160	1086	282	39.0	10km/h 30km/h 40km/h 50km/h	860 710 665 615	1005 825 775 715	1150 945 885 815 1420 1170	1290 1060 995 915	1180 1105 1015	1575 1300 1215 1120						
320/85R24	122/119	A8/B	W9W10W11	1500	160	1154	319	41.0	10km/h 30km/h 40km/h 50km/h	1070 880 825 745	1245 1025 960 870	1095 990	1595 1315 1230 1115	1770 1460 1365 1235	1950 1605 1500 1360						
320/85R28	124/121	A8/B	W9W10W11	1600	160	1255	319	41.0	10km/h 30km/h 40km/h 50km/h	1140 940 880 795	1325 1090 1020 925 1410	1510 1245 1165 1055	1700 1400 1310 1185	1890 1555 1455 1315	2080 1710 1600 1450						
320/85R32	126/123	A8/B	W9W10W11	1700	160	1357	319	41.0	10km/h 30km/h 40km/h 50km/h	1215 1000 935 850	1160 1085 990	1610 1325 1240 1130	1805 1485 1390 1270	2005 1650 1545 1410	2210 1815 1700 1550						
320/85R32	142/139	A8/B	W9W10W11	2650	400	1357	319	41.0	10km/h 30km/h 40km/h 50km/h	1205 990 925 850	1410 1160 1085 995	1615 1330 1245 1140	1825 1500 1400 1285	2030 1670 1560 1430	2200 1810 1695 1555	2445 2010 1880 1725	2580 2125 1985 1820	3065 2520 2355 2160	3065 2520 2355 2160	3270 2690 2515 2305	3445 2835 2650 2430
320/85R36	128/125	A8/B	W9W10W11	1800	160	1458	319	41.0	10km/h 30km/h 40km/h 50km/h	1285 1055 990 905	1495 1230 1150 1055 1370	1700 1400 1310 1200	1575 1475 1350	2125 1745 1635 1500	2340 1925 1800 1650						
340/85R24	125/122	A8/B	W11W12	1650	160	1188	343	42.0	10km/h 30km/h 40km/h 50km/h	965 905 825	1370 1125 1055 960 1455	1560 1280 1200 1095 1655	1755 1440 1350 1230	1950 1605 1500 1365	2145 1765 1650 1500 2275						
340/85R28	127/124	A8/B	W11W12	1750	160	1289	343	42.0	10km/h 30km/h 40km/h 50km/h	1245 1025 960 880	1195 1120 1020	1360 1275 1165	1865 1535 1435 1310	2065 1700 1590 1455	1870 1750 1600						
340/85R32	142/139	A8/B	W11W12	2650	360	1391	343	42.0	10km/h 30km/h 40km/h 50km/h	1275 1045 980 895	1480 1215 1135 1045	1685 1385 1295 1190	1925 1585 1485 1360	2135 1755 1640 1505	1800 1650	1985	2235 2090	2465 2305	2665 2490	3445 2835 2650 2430	
340/85R36	132/129	A8/B	W11W12	2000	160	1492	343	42.0	10km/h 30km/h 40km/h 50km/h	1175 1100 1015	1660 1365 1280 1180	1560 1460 1350	1755 1640 1515	2365 1945 1820 1680	2600 2140 2000 1850						
340/85R38	133/130	A8/B	W11W12	2060	160	1543	343	42.0	10km/h 30km/h 40km/h 50km/h	1465 1205 1130 1045	1705 1405 1315 1215	1605 1500 1385	2190 1800 1685 1555	2430 2000 1870 1725	2675 2200 2060 1900						
380/85R24	131/128	A8/B	W11W12W13	1950	160	1256	380	45.0	10km/h 30km/h 40km/h 50km/h	1390 1140 1070 990	1615 1330 1245 1150	1845 1515 1420 1310	2070 1705 1595 1475	2300 1890 1770 1635	2535 2085 1950 1800						
380/85R28	133/130	A8/B	W11W12W13	2060	160	1357	380	45.0	50km/h	1465 1205 1130 1045	1705 1405 1315 1215	1950 1605 1500 1385	2190 1800 1685 1555	2430 2000 1870 1725	2675 2200 2060 1900						
380/85R30	135/132	A8/B	W11W12W13	2180	160	1408	380	45.0	10km/h 30km/h 40km/h 50km/h	1550 1275 1195 1100	1810 1490 1395 1280	2065 1700 1590 1460	2320 1905 1785 1640	2570 2115 1980 1820	2830 2330 2180 2000						
380/85R34	137/137	A8/B	W11W12W13	2300	160	1510	380	45.0	10km/h 30km/h 40km/h 50km/h	1350 1265 1265	1570 1470 1470	1790 1675 1675	1885	2235 2090 2090	2990 2460 2300 2300						
380/85R34	147/147	A8/B	W11W12W13	3075	240	1510	380	45.0	10km/h 30km/h 40km/h 50km/h	1875 1545 1445 1445	1660	2035	2795 2300 2150 2150	3110 2560 2395 2395	2640	3755 3090 2890 2890	3290 3075				



LR861 Radial Agricultural Tire

- 1. Better traction and braking performance.
- 2. Save work time and fuel.
- 3. Better running stability.
- 4. Suitable for modern mechanical equipment.

Size	Load	Speed	Rim	Max.Load	Inflated	Overall Diameter	Section Width	Tread Depth			I	Press	ure((kPa)	-Load	d per	tyre	in ko	3		
3120	Index	Speed Symbols	NIII	(kg)	(kPa)	(mm)	(mm)	(mm)	kPa	60							240	280	320	360	400
420/85R24	137/134	A8/B	W13W14LW15L	2300	160	1324	418	48.0	10km/h 30km/h 40km/h 50km/h 10km/h 30km/h 40km/h 50km/h 10km/h 40km/h 10km/h	1640 1350 1265 1165	1910 1570 1470 1355	2175 1790 1675 1545	2450 2015 1885 1735	2715 2235 2090 1925	2990 2460 2300 2120						
420/85R28	139/136	A8/B	W13W14LW15L	2430	160	1425	418	48.0	10km/h 30km/h 40km/h 50km/h	1735 1425 1335 1230	2020 1660 1555 1430	2300 1890 1770 1635	2585 2125 1990 1835	2870 2360 2210 2035	3155 2600 2430 2240						
420/85R30	140/137	A8/B	W13W14LW15L	2500	160	1476	418	48.0	10km/h 30km/h 40km/h 50km/h	1785 1470 1375 1265	2080 1710 1600 1470	2370 1950 1825 1675	2665 2190 2050 1885	2955 2430 2275 2090	3250 2675 2500 2300						
420/85R34	142/139	A8/B	W13W14LW15L	2650	160	1578	418	48.0	10km/h 30km/h 40km/h 50km/h	1890 1555 1455 1335	2200 1810 1695 1555	2505 2065 1930 1770	2820 2320 2170 1990	3130 2575 2410 2210	3445 2835 2650 2430						
420/85R38	144/141	A8/B	W13W14LW15L	2800	160	1679	418	48.0	30km/h 40km/h 10km/h 30km/h 40km/h 10km/h 10km/h 10km/h 40km/h 10km/h 30km/h 40km/h 50km/h 10km/h 30km/h 40km/h 50km/h 10km/h 30km/h 40km/h 50km/h 10km/h 30km/h 40km/h 10km/h	2000 1645 1540 1415	2325 1915 1790 1645	2650 2180 2040 1875	2980 2455 2295 2110	3305 2720 2545 2340	3640 2995 2800 2575						
460/85R30	145/142	A8/B	W14LW15LW16L	2900	160	1544	455	51.0	10km/h 30km/h 40km/h 50km/h	2070 1705 1595 1455	2410 1980 1855 1695	2745 2260 2115 1930	3085 2540 2375 2170	3425 2815 2635 2410	3770 3100 2900 2650						
460/85R34	147/144	A8/B	W14LW15LW16L	3075	160	1646	455	51.0	10km/h 30km/h 40km/h 50km/h	2195 1805 1690 1540	2550 2100 1965 1790	2910 2395 2240 2040	3275 2695 2520 2295	3630 2990 2795 2545	3995 3290 3075 2800						
460/85R38	149/146	A8/B	W14LW15LW16L	3250	160	1747	455	51.0	10km/h 30km/h 40km/h 50km/h	2320 1905 1785 1650	2700 2225 2080 1920	3080 2535 2370 2190	3460 2850 2665 2460	3840 3160 2955 2730	4225 3475 3250 3000						
460/85R42	150/147	A8/B	W14LW15LW16L	3350	160	1849	455	51.0	10km/h 30km/h 40km/h 50km/h	2390 1965 1840 1690	2780 2285 2140 1965	3175 2615 2445 2240	3565 2935 2745 2520	3955 3255 3045 2795	4355 3580 3350 3075						
460/85R46	152/149	A8/B	W14L	3550	160	1943	464	51.0	40km/h	1950	2270	2590	2910	3230	3550						
460/85R46	158/155	A8/B	W14L	4250	240	1943	464	51.0	50km/h 10km/h 30km/h 40km/h 50km/h 10km/h 30km/h 40km/h 10km/h 30km/h 40km/h 10km/h	2595 2135 1995 1820	2980 2455 2295 2090	3425 2815 2635 2400	3865 3180 2975 2710	4305 3545 3315 3020	4750 3910 3655 3330	5190 4275 3995 3640	5525 4545 4250 3875				
520/85R38	155/152	A8/B	DW16L DW18L	3875	160	1849	516	54.0	10km/h 30km/h 40km/h 50km/h	2765 2275 2130 1950	3220 2650 2480 2270	3670 3020 2825 2590	4125 3395 3175 2910	4580 3770 3525 3230	5035 4145 3875 3550						
520/85R42	157/154	A8/B	DW16L DW18L	4125	160	1951	516	54.0	10km/h 30km/h 40km/h 50km/h	2940 2420 2265 2060	3430 2820 2640 2400	3910 3220 3010 2735	4390 3615 3380 3075	4875 4010 3750 3410	5360 4410 4125 3750						
520/85R42	167/164	A8/B	DW16L DW18L	5450	320	1951	516									5525 4545 4250 3865	6090 5010 4685 4260	6655 5480 5120 4660	5450		
420/80R46	145/142	A8/B	W12W13	2900	160	1840	418	47.0	10km/h 30km/h 40km/h 50km/h	2070 1705 1595 1455	2410 1980 1855 1695	2745 2260 2115 1930	3085 2540 2375 2170	3425 2815 2635 2410	3770 3100 2900 2650						
420/80R46	151/148	A8/B	W12W13	3450	240	1840	418	47.0	30km/h 40km/h 50km/h 10km/h 30km/h 40km/h 50km/h 10km/h 30km/h 40km/h 50km/h	2107 1734 1621 1524	2421 1993 1863 1751	2780 2288 2139 2010	3139 2583 2415 2270	3498 2878 2691 2529	3857 3174 2967 2788	4215 3469 3243 3048	3691 3450 3243				



LR861 Radial Agricultural Tire

- 1. Better traction and braking performance.
- 2. Save work time and fuel.
- 3. Better running stability.4. Suitable for modern mechanical equipment.

Size	Load	Speed	Rim	Max.Load	Inflated Pressure	Overall Diameter	Section Width	Tread Depth			ا	Pres	sure((kPa)-	Loac	l per	tyre	in kg			
3.20	Index	Symbols		(kg)	(kPa)	(mm)	(mm)	(mm)	kPa	60						200	240	280	320	360	400
480/80R42	151/151	A8/B	DD16L DW16L W16L DW16A* W16A*	3450	160	1835	479	49.0	10km/h 30km/h 40km/h 50km/h	1895	2355 2205 2205	2690 2515 2515	3020 2825 2825	4075 3350 3135 3135	3690 3450 3450						
480/80R42	156/156	A8/B	DD16LDW16LW16LDW16A*W16A*	4000	240	1835	479	49.0	40km/h 50km/h	2440 2010 1880 1880	2160 2160	2480 2480	2995 2800 2800	3335 3120 3120	3680 3440 3440	4280 4000 4000					
480/80R46	158/158	A8/B	DD16LDW16LW16LDW16A*W16A*	4250	240	1936	479	49.0	10km/h 30km/h 40km/h 50km/h	1995 1995	2295 2295	2635 2635	3180 2975 2975	3315 3315	3655 3655	4545 4250					
420/90R30	142/139	A8/B	DW13W14L	2650	160	1518	418	48.0	10km/h 30km/h 40km/h 50km/h	1455 1335	1695 1555	2065 1930 1770	2320 2170 1990		2835 2650 2430						
420/90R30	147/144	A8/B	DW13W14L	3075	240	1518	418	48.0	10km/h 30km/h 40km/h 50km/h	1445 1315	1660 1510	1905 1735	2300 2150 1960	2560 2395 2180	2820 2640 2405	3290 3075 2800					
320/90R46(R-1)	146/143	A8/B	W9W10W11	3000	320	1744	319	37.0	10km/h 30km/h 40km/h 50km/h		1380 1250	1590 1440	1890 1770 1605	2115 1980 1795	2310 2160 1960	2315	2985 2790 2530		3900 3210 3000 2725		
320/90R46(R-1)	148/148	A8/B	W9W10W11	3150	360	1744	319	37.0	10km/h 30km/h 40km/h 50km/h	1515 1246 1165 1060	1232	2006 1651 1543 1404	1887 1764 1604	2089 1953 1776	2291 2142 1948	3235 2662 2488 2264	2931 2740		2961	4095 3370 3150 2866	
380/90R46	149/149	A8/B	W11W12W13	3250	240	1852	380	45.0	10km/h 30km/h 40km/h 50km/h	1525	1755 1755	2015	2430 2275 2275	2535 2535	2990 2795 2795	3250 3250					
380/90R46	157/157	A8/B	W11W12W13	4125	360	1852	380	45.0	10km/h 30km/h 40km/h 50km/h	1980 1630 1525 1525	1770	2020	2465 2310	2730 2555	2995 2805	4230 3480 3255 3255	3835 3585	:	5035 4145 3875 3875	4410 4125	



LR700 Radial Agricultural Tire

- 1. Saving time and fuel.
- Better self-cleaning capability.
 Comfort on the road and in the field.

Size	Load	Speed	Rim	Max.Load	Proceuro	Diameter	Width	Depth			I	Press	sure(kPa)-	Loac	d per	tyre	in ko)		
SIZC	Index	Speed Symbols	KIIII	(kg)	(kPa)	(mm)	(mm)	(mm)	kPa	60	80	100	120	140	160	200	240	280	320	360	400
280/70R20	116/113	A8/B	W9 W10	1250	240	900	282	35.5	10km/h 30km/h 40km/h 50km/h 10km/h 30km/h 50km/h 10km/h 30km/h 40km/h 50km/h 10km/h 30km/h 10km/h	1210 905 855 750	1385 1035 975 860	1520 1135 1070 945	1555 1160 1095 1040	1580 1180 1115 1060	1620 1210 1140 1085	1650 1230 1160 1105	1775 1325 1250 1160				
360/70R24	122/119	A8/B	W10W11W12	1500	160	1152	357	42.0	10km/h 30km/h 40km/h 50km/h	1070 880 825 745	1245 1025 960 870	1420 1170 1095 990	1595 1315 1230 1115	1770 1460 1365 1235	1950 1605 1500 1360						
360/70R24	127/124	A8/B	W10W11W12	1750	240	1152	357	42.0	10km/h 30km/h 40km/h 50km/h	1065 875 820 750	1225 1010 945 860	1410 1160 1085 990	1590 1310 1225 1120	1770 1460 1365 1245	1955 1610 1505 1375	2135 1760 1645 1500	2275 1870 1750 1600				
380/70R24	125/125	A8/B	W11W12W13	1650	160	1190	380	43.0	10km/h 30km/h 40km/h 50km/h	2070 1705 1595 905	2410 1980 1855 1055	2745 2260 2115 1200	3085 2540 2375 1350	3425 2815 2635 1500	3770 3100 2900 1650						
420/70R24	130/127	A8/B	W12W13W14L	1900	160	1248	418	44.0	30km/h 40km/h 50km/h	1115 1045 960	1300 1215 1120	1480 1385 1275	1660 1555 1435	1845 1725 1590	1900 1750						
420/70R24	136/133	A8/B	W12W13W14L	2240	240	1248	418	44.0	10km/h 30km/h 40km/h 50km/h	1120 1050	1285 1205	1385	1670 1565	1865 1745	2500 2055 1925 1770	2250	2910 2395 2240 2060				
420/70R28	133/130	A8/B	W12W13W14L	2060	160	1349	418	44.0	50km/h 10km/h 30km/h 40km/h 50km/h 10km/h 30km/h 40km/h 10km/h 30km/h 40km/h 10km/h	1465 1205 1130 1045	1705 1405 1315 1215	1950 1605 1500 1385	2190 1800 1685 1555	2430 2000 1870 1725	2675 2200 2060 1900						
420/70R28	139/136	A8/B	W12W13W14L	2430	240	1349	418	44.0	10km/h 30km/h 40km/h 50km/h	1480 1215 1140 1050	1700 1400 1310 1205	1955 1610 1505 1385	2210 1815 1700 1565	2460 2025 1895 1745 2785 2295 2145 1980	2710 2230 2085 1925	2960 2435 2280 2105	3155 2600 2430 2240				
480/70R24	138/135	A8/B	W14LW15LW16L	2360	160	1316	479	47.0	10km/h 30km/h 40km/h 50km/h	1680 1385 1295 1195	1960 1615 1510 1395	2235 1840 1720 1590	2515 2070 1935 1785	2785 2295 2145 1980	3065 2525 2360 2180						
480/70R28	140/137	A8/B	W14LW15LW16L	2500	160	1421	479	47.0	30km/h 40km/h 50km/h	1470 1375 1265	1710 1600 1470	1950 1825 1675	2190 2050 1885	2430 2275 2090	2675 2500 2300						
480/70R28	145/142	A8/B	W14LW15LW16L	2900	240	1421	479	47.0	10km/h 30km/h 40km/h	1770 1455 1360 1245	1670 1565 1430	1920 1795 1640	2635 2170 2030 1855	2940 2415 2260 2065	2665 2490	2910 2725 2490	3100 2900 2650	4170 3430 3205 3015	3690 3450		
480/70R28	151/148	A8/B	W14LW15LW16L	3450	320	1421	479	47.0	10km/h 30km/h 40km/h 50km/h	1745 1435 1345 1260	2060 1695 1585 1490	1955 1825 1715	2645 2175 2035 1910	2960 2435 2275 2140	3225 2655 2480 2330	3540 2915 2725 2560	3810 3135 2930 2755				
480/70R34	143/143	A8/B	W14LW15LW16L	2725	160	1580	479	47.0	10km/h 30km/h 40km/h 50km/h	1940 1595 1495 1495	1860 1740 1740	2580 2120 1985 1985	2895 2385 2230 2230	3215 2645 2475 2475	3540 2915 2725 2725						
480/70R38	145/142	A8/B	W14LW15LW16L	2900	160	1681	479	47.0	10km/h 30km/h 40km/h 50km/h 10km/h 30km/h 40km/h	2070 1705 1595 1455	2410 1980 1855 1695	2745 2260 2115 1930	3085 2540 2375 2170	3425 2815 2635 2410	3770 3100 2900 2650						
520/70R38	150/150	A8/B	W15LW16LW18L	3350	160	1749	516	48.0	30km/h 40km/h 50km/h	2025 1895	2355 2205 2205	2690 2515 2515	3020 2825 2825	3350 3135 3135	3690 3450 3450						
580/70R38	155/155	A8/B	W18L	3875	160	1827	577	50.0	10km/h 30km/h 40km/h 50km/h	2765 2275 2130 2130	3220 2650 2480 2480	3670 3020 2825 2825	4125 3395 3175 3175	3770 3525 3525	5035 4145 3875 3875			7800 6420 6000 5450			
580/70R38	170/167	A8/B	W18L	6000	280	1827	577	50.0	10km/h 30km/h 40km/h 50km/h	2760 2580	3900 3210 3000	3655 3420	4980 4100 3840	4555 4260	5005 4680	5520 5160	5840 5460				



LR650 Radial Agricultural Tire

- Longer service life.
 Excellent stability and comfort.
- 3. More efficient traction.
- 4. Outstanding floating behavior reduces pressure to land.

Size	Load	Speed	Rim	Max.Load	Inflated Pressure	Overall Diameter	Section Width	Tread Depth			ا	Press	sure((kPa)	-Load	d per	tyre	in kç	J		
	Index	Symbols		(kg)	(kPa)	(mm)	(mm)	(mm)	kPa	60						200	240	280	320	360	400
440/65R24	128/131	D/A8	W13W14L W15L	1800	160	1182	441	45.0	10km/h 30km/h 40km/h 50km/h 65km/h	1055	1540 1365 1285 1245 1185	1755 1550 1460 1415 1350	1585	1735	1890 1800						
440/65R28	131/134	D/A8	W13W14L W15L	1950	160	1283	441	45.0	10km/h 30km/h 40km/h 50km/h 65km/h		1285	1900 1680 1590 1530 1460	1880 1780 1715 1635	11790	1950						
480/65R24	133/136	D/A8	W14LW15L	2060	160	1234	479	46.0	10km/h 30km/h 40km/h 50km/h 65km/h	1495 1320 1250 1205 1150	1765 1560 1475 1425 1355	2005 1770 1680 1620 1545	1810 1730	2060 1985 1895	2160 2060						
480/65R28	136/139	D/A8	W14LW15L	2240	160	1335	479	46.0	10km/h 30km/h 40km/h	1625 1440 1360	1920 1695 1600	1930 1820	2160 2040 1970 1880	2235 2160 2060	2910 2575 2430 2350 2240						
540/65R24	140/143	D/A8	W16LW18L	2500	160	1312	550	48.0	65km/h 10km/h 30km/h 40km/h 50km/h 65km/h	14/0	1650	1905	2730 2415 2285 2205 2100	2990 2645 2505 2415 2300	3250 2875 2725 2625 2500						
540/65R28	142/145	D/A8	W16LW18L	2650	160	1413	550	48.0	10km/h 30km/h 40km/h 50km/h 65km/h	1705 1620 1555 1480	1745	1985	2335	2800 2665 2555 2435	3445 3045 2900 2780 2650						
540/65R30	150/153	D/A8	W16LW18L	3350	240	1464	550	48.0	10km/h 30km/h 40km/h 50km/h 65km/h	2045 1805 1715 1650 1570	2395 2115 2005 1930 1840	2740	3045	2060	3610 3195 3025	4050 3580 3390 3265 3115	4355 3850 3650 3515 3350				
540/65R34	145/148	D/A8	W16LW18L	2900	160	1566	550	48.0	10km/h 30km/h 40km/h 50km/h 65km/h	1865 1760	2485 2200 2075	2825 2500 2360 2280 2175	3165 2800 2645	3465 3065 2895	3770 3335 3150						
540/65R38	153/156	D/A8	W16LW18L	3650	240	1667	550	48.0	10km/h 30km/h 40km/h 50km/h	1970 1865 1800	2605 2305 2185 2105	2980 2635 2500 2405	3320 2935 2780 2680	3650 3230 3060 2950	3930 3475	3695 3555	4745 4195 3975 3820 3650				
600/65R28	147/150	D/A8	DW20BW18L	3075	160	1491	591	52.0	10km/h 30km/h 40km/h 50km/h	2235 1975 1875 1805 1720	2635 2330 2210 2125 2025	2995 2650 2510 2415 2305	3355 2965 2810 2705 2580	3675 3250 3080 2965 2825	3995 3535						
600/65R34	157/160	D/A8	DW20BW18L	4125	240	1644	591	52.0	10km/h 30km/h 40km/h 50km/h 65km/h	2515 2225 2105 2030 1935	2940 2600 2465 2375 2265	3370	3750	4125 3650	4445 3930	4985 4410 4180 4025 3835	4330				
600/65R38	153/156	D/A8	DW20BW18L	3650	160	1745	591	52.0	10km/h 30km/h 40km/h	2655 2345 2240	3130 2765 2640	3555 3145 3000	3985 3520 3360 3215 3065	4365 3855 3680 3520 3355	4745 4195 4000 3830 3650						
650/65R38	157/160	D/A8	DW20B	4125	160	1811	645	56.0	65km/h 10km/h 30km/h 40km/h 50km/h	2520	2970	4020 3555 3375 3245 3090	4500 3980 3780 3635 3465	4140	5360 4740 4500						
650/65R42	165/168	D/A8	DW20B	5150	240	1913	645	56.0	65km/h 10km/h 30km/h 40km/h 50km/h 65km/h	2780	3680	4215 3725 3525 3405 3240	4685 4140 3920	5155 4555 4310	5555 4910 4645	6225 5505 5205 5025 4785	6695 5920 5600 5405				
710/70R38	166/169	D/A8	DW23B	5300	160	1959	716	57.0	10km/h	3855 3410	4545	5165	5785 5115	6335 5605	6890 6095 5800 5565 5300						
710/70R42	168/171	D/A8	DW23B	5600	160	2061	716	57.0	10km/h 30km/h	3605 3440	4800 4250 4055	5460 4830 4610 4410 4200	6115 5405 5165 4935	5920 5655	7280 6440 6150 5880 5600						
710/70R42	173/176	D/A8	DW23B	6500	240	2061	716	57.0	10km/h 30km/h 40km/h	3970 3510 3335 3205	4645 4110 3905 3750	5320 4705 4470 4295	5915 5230 4970 4775	6505 5755 5465 5255	7010 6200 5890 5660 5395	6950	8450 7475 7100 6825 6500				





LR8000 Radial Agricultural Tire

- 1. Longer service life.
- 2. Excellent stability and comfort.
- 3. More efficient traction.
- 4. Outstanding floating behavior reduces pressure to land.

Size	Load	Speed	Rim	Max.Load	Inflated Pressure	Overall Diameter	Section Width	Tread Depth				Press	ure(l	kPa)-	-Loac	d per	tyre	in kç	J		
3.20	Index	Symbols	1,111	(kg)	(kPa)	(mm)	(mm)	(mm)	kPa	60	80				1	200	240	280	320	360	400
800/65R32	167	D	DW25B DW27B DH27B	5450	160	1853	798	58.0	10km/h 30km/h 40km/h 50km/h 65km/h			4700 4475 4290 4085	5010 4805 4575	5765 5485 5260 5010	6265 5965 5720 5450						
800/65R32	172	D	DW25B DW27B DH27B	6300	240	1853	798	58.0	10km/h 30km/h 40km/h 50km/h 65km/h			4560 4345 4165 3965	5070 4825 4630 4410	5575 5310 5090 4850	6010 5725 5490 5225	7615 6735 6415 6150 5855	7245 6895 6615 6300				
800/65R32	178	D	DW25B DW27B DH27B	7500	320	1853	798	58.0	10km/h 30km/h 40km/h 50km/h 65km/h			4245 4045 3875 3695	4740 4515 4330 4125	5405 5145 4935 4700	6060 5770 5530 5270	6725 6405 6140 5850	7715 7345 7045 6710	9230 8165 7770 7455 7100	8625 8212 7875 7500		
800/65R32	181/181	A8/B	DW25B DW27B DH27B	8250	360	1853	798	58.0	10km/h 30km/h 40km/h 50km/h			4325 4040	4940 4620	5470 5115	6000 5610	6620 6185	6970 6515	7675 7175	10080 8295 7755 7755	8825 8250	



LR7000 Radial Agricultural Tire

- Up to 10% load.
 Enhance bead strength.
 Longer service life.
 Excellent stability and comfort.
 More efficient traction.
 Outstanding floating behavior reduces pressure to land.

Size	Load	Speed	Rim	Max.Load	Inflated Pressure	Overall Diameter	Section Width	Tread Depth			ا	Press	ure(l	kPa)-	Loac	l per	tyre	in kg	3		
3120	Index	Symbols	1	(kg)	(kPa)	(mm)	(mm)	(mm)	kPa									280	320	360	400
600/70R28	157	D	DW18L DW20BW18L	4125	240	1551	591	52.5	10km/h 30km/h 40km/h 50km/h 65km/h	2225 2120 2035 1935	2605 2480 2380 2265	2985 2845 2725 2595	3320 3160 3030 2885	3650 3475 3330 3175	3935 3745 3590 3420	4410 4195 4025 3835	4740 4515 4330 4125				
600/70R28	161/161	A8/B	DW18L DW20BW18L	4625	280	1551	591	52.5	10km/h 30km/h 40km/h 50km/h 10km/h	2125 1985 1985 2580	2470 2310 2310 3045	2820 2635 2635 3460	3165 2960 2960 3875	3510 3280 3280 4245	3855 3605 3605 4615	4255 3975 3975	4500 4205	4945 4625			
600/70R30	152	D	DW18L DW20B W18L	3550	160	1602	591	52.5	30km/h 40km/h 50km/h 65km/h 10km/h	2175 2085 1985 2595	2565 2455 2340 2980	2915 2795 2660 3425	3265 3130 2980 3865	3575 3425 3265 4305	3885 3725 3550 4750	5190					
600/70R30	158	D	DW18L DW20BW18L	4250	240	1602	591	52.5	30km/h 40km/h 50km/h 65km/h 10km/h	2185 2095 1995 3970	2510 2405 2295 4645	2880 2765 2635 5320	3255 3120 2975 5915	3625 3480 3315 6505	4000 3835 3655 7010	4370 4190 3995 7855	4650 4460 4250 8450				
650/85R38	173/176	D/A8	DW20B DW21B DW23B	6500	240	2071	645	65.0	30km/h 40km/h 50km/h 65km/h	3325 3205	3895 3750	4460 4295	4955 4775	5455 5255	5880 5660	6585 6345	7085 6825				





LR9000 Radial Agricultural Tire

- Better soil protection.
 Exceptional load capacity.

Size	Load	Speed	Rim	Max.Load	Inflated Pressure	Overall Diameter	Section Width				F	ress	ure(l	кРа)-	Loac	l per	tyre	in kg	ı		
0.20	Index	Symbols		(kg)	(kPa)	(mm)	(mm)	(mm)	kPa									280	320	360	400
380/90R50	151/151	A8/B	W11W12W13	3450	240	1954	380	48.0	10km/h 30km/h 40km/h 50km/h	1710 1600 1600	1975 1850 1850	2265 2120 2120	2525 2360 2360	2835 2650 2650	3100 2900 2900	3370 3150 3150	3690 3450 3450				
380/90R50	160/157	A8/B	W11W12W13	4500	400	1954	380	48.0	10km/h 30km/h 40km/h 50km/h	1685 1575	1970 1845	2260 2115	2550 2385	2840 2655	3080 2880	3415 3195	3610 3375	3945 3690	4285 4005	4570 4275	4815 4500



LR861 Radial Agricultural Tire

- 1. Better traction and braking performance.
- 2. Save work time and fuel.
- 3. Better running stability.
- 4. Suitable for modern mechanical equipment.

Size	Load	Speed	Rim	Max.Load	Inflated Pressure	Overall Diameter	Section Width	Tread Depth	pthPressure(kPa)-Load per tyre in kg											
3120	Index	Symbols	111	(kg)	(kPa)	(mm)	(mm)	(mm)	kPa 6										360 4	100
320/90R46(R-1)	146/143	A8/B	W9W10W11	3000	320	1744	319	37.0	30km/h 12 40km/h 11 50km/h 10	50 14 70 13 60 12	75 170 30 159 50 144	1770	2115 1980 1795	2310 2160 1960	2535 2370 2150	2725 2550 2315	2985 2790 2530	3210 3000 2725		
320/90R46(R-1)	148/148	A8/B	W9W10W11	3150	360	1744	319	37.0	10km/h 15 30km/h 12 40km/h 11 50km/h 11	45 14 65 13	15 165 50 154	1885 1760	2085 1950	2290 2140	2525 2360	2660 2485	2930 2740	3165 2960	3370 3150	
340/85R38	133/130	A8/B	W11W12	2060	160	1543	343	42.0	10km/h 14 30km/h 12 40km/h 11 50km/h 10	05 14 30 13 45 12	05 160 15 150 15 138	1800 1685 1555	2000 1870 1725	2200 2060 1900						
380/90R46	149/149	A8/B	W11W12W13	3250	240	1852	380	45.0	10km/h 19 30km/h 16 40km/h 15 50km/h 15	30 18 25 17 25 17	75 215 55 201 55 201	2275	2710 2535 2535	2990 2795 2795	3265 3055 3055	3475 3250 3250				
380/90R46	157/157	A8/B	W11W12W13	4125	360	1852	380	45.0	10km/h 19 30km/h 16 40km/h 15 50km/h 15	30 18 25 17	95 216 70 202	2465	2730 2555	2995 2805	3305 3090	3480 3255	3835 3585	4145 3875	4410 4125	





LBI301 Radial Agricultural Tire

- 1. Longer service life.
- 2. Excellent stability and comfort.
- 3. More efficient traction.
- 4. Outstanding floating behavior reduces pressure to land.

Size	Load	Speed	Rim	Max.Load	Inflated Pressure	Overall Diameter	Section Width				ŀ	Press	ure(ŀ	(Pa)-	Load	l per	tyre	in kg			
0.20	Index	Symbols		(kg)	(kPa)	(mm)	(mm)	(mm)													
600/50R22.5IMP	159	D	AG20.00	4375	400	1172	611	25.0	30km/h 40km/h 50km/h 65km/h	1760 1675 1605	2060 1960 1880 1790	2360 2250 2155 2055	2665 2535 2430 2315	2965 2825 2705 2580	3215 3065 2935 2800	3400 3260 3105	3770 3590 3440 3280	4125 3925 3765 3585	4475 4260 4085 3890	4775 4550 4360 4155	5030 4790 4590 4375
650/65R30.5IMP	176	D	AG20.00	7100	400	1621	645	32.0	10km/h 30km/h 40km/h 50km/h 65km/h			4900 4280 3790 3170	5495 4785 4245 3540	6395 5545 4920 4090	7290 6305 5600 4645	9055 7885 6810 6055 5015	9080 7820 6960 5750	9615 8280 7370 6090	10150 8740 7775 6425	10685 9200 8180 6760	11220 9660 8590 7100
850/50R30.5IMP	182	D	AG28.00	8500	400	1625	862	32.0	10km/h 30km/h 40km/h 50km/h 65km/h			5370 4620 4110	6035 5190 4620	7025 6050 5380	8020 6905 6145	9995 8685 7475 6655 5500	10010 8620 7670	10865 9355 8325	11720 10090 8980	12575 10825 9635	13430 11560 10290



FL300 Radial Agricultural Tire

- 1. Steel belted construction.
- 2. Good wear resistance.
- 3. Good ride-comfort performance.

Size	Load	Speed	Rim	Max.Load	Inflated Pressure	Overall Diameter	Section Width	Tread Depth	th												
5.20	Index	Symbols	1,111	(kg)	(kPa)	(mm)	(mm)	(mm)													
500/60R22.5IMP	155	D	AG16.00	3875	400	1172	503	18.0	10km/h 30km/h 40km/h 50km/h 65km/h	2045 1845	2395 2160 1920	2750 2475 2200 1820	3100 2790 2485 2050	3450 3105 2765 2285	3745 3370 3000 2480	4155 3740 3325 2750	4385 3950 3515 2905	5715 4795 4320 3845 3175	5205 4690 4170 3445	5555 5005 4455 3680	5850 5270 4685 3875
560/60R22.5IMP	165	D	AG16.00 16.00 17.00 AG20.00	5150	500	1244	543	18.0	10km/h 30km/h 40km/h 50km/h 65km/h			2485 2210 1825	3060 2755 2455 2025	3165 2815 2330	3975 3580 3185 2635	4285 3855 3430 2835	4890 4405 3920 3240	6560 5500 4955 4410 3645	6110 5505 4895 4045	6720 6055 5385 4450	7335 6605 5875 4855
560/45R22.5IMP	152	D	AG16.00	3550	400	1076	543	18.0	10km/h 30km/h 40km/h 50km/h 65km/h	1685 1500	2195 1975	2515 2265 2015 1665	2840 2555 2275 1880	3160 2845 2535 2095	3430 3085 2745 2270	3805 3425 3045 2520	4020 3620 3220 2660	2910	4770 4295 3820 3155	4080 3370	5360 4825 4295 3550
600/55R26.5IMP	165	D	AG20.00	5150	400	1333	611	20.0	10km/h 30km/h 40km/h 50km/h 65km/h			3560 3100 2750 2300	3465 3080 2565	3570 2970	5290 4570 4065 3370	5725 4935 4395 3635	6590 5670 5050 4170	7950 6980 6000 5345 4415	7365 6335 5640 4660	7750 6670 5935 4905	8140 7000 6230 5150
650/55R26.5IMP	169	D	AG20.00	5800	400	1389	645	24.0	10km/h 30km/h 40km/h 50km/h 65km/h			3910 3520 3130 2590	4635 4175 3710 3070	5050 4545 4045 3345	5720 5150 4585 3790	6175 5560 4945 4090	7085 6385 5680 4695	8955 7510 6765 6015 4975	7915 7130 6345 5245	7510 6685 5525	8755 7885 7015 5800
710/50R26.5IMP	170	D	AG20.00 AG24.00	6000	400	1383	727	24.0	10km/h 30km/h 40km/h 50km/h 65km/h			3610 3200 2680	4645 4040 3585 2990	4680 4155 3460	6155 5325 4730 3925	6660 5755 5115 4235	7670 6610 5880 4860	9260 8120 7000 6225 5145	8575 7385 6570 5430	5715	9480 8160 7260 6000
710/50R30.5IMP	173	D	AG20.00 AG24.00	6500	400	1485	727	26.0	10km/h 30km/h 40km/h 50km/h 65km/h			4490 3910 3470	5035 4375 3885	5070 4505	6675 5765 5125	7220 6230 5540	8310 7160 6370	10035 8800 7580 6745 5580	10590 9290 8000 7120	11145 9780 8420 7495	11700 10270 8840 7870





LR451 Radial Agricultural Tire

- 1. Increase traction performance.
- 2. Enhance shoulder wear and cut resistance performance.
- 3. Enhance tread wear resistance performance.

Size	Load	Speed	Rim	Max.Load	Inflated Pressure	Overall Diameter	Section Width	Tread Depth			ا	ress	ure(l	kPa)-	Loac	l per	tyre	in ko	J		
3.20	Index	Symbols		(kg)	(kPa)	(mm)	(mm)	(mm)	kPa	60						200	240	280	320	360	400
460/70R24 IND	152/152	A8/B	DW14L DW15L DW16L	3550	320	1254	455	36.0	0km/h 10km/h 30km/h 40km/h 50km/h	2575 2140 2060	2800 2330 2240	2530 2430	3500 2910 2800	4060 3380 3250	4435 3690 3550						
460/70R24 IND	159/159	A8/B	DW14L DW15L DW16L	4375	400	1254	455	36.0	0km/h 10km/h 30km/h 40km/h 50km/h							3040 2525 2430	3500 2910 2800	4060 3380 3250	4440 3690 3550	9200 5000 4160 4000 4000	5470 4550 4375
500/70R24 IND	164/164	A8/B	DW16LDW15L	5000	400	1302	511	39.0	0km/h 10km/h 30km/h 40km/h 50km/h	2625 1870 1750	3075 2190 2050	2515 2350	3975 2835 2650	4425 3155 2950	4800 3420 3200	5325 3795 3550	5625 4010 3750	6150 4385 4100	6675 4760 4450	5080 4750	7500 5350 5000



LR400 Radial Agricultural Tire

- 1. Increase traction performance.
- 2. Enhance shoulder wear and cut resistance performance.
- 3. Enhance tread wear resistance performance.

Size	Load	Speed	Rim	Max.Load	Inflated Pressure	Overall Diameter	Section Width				ı	Press	ure(l	кРа)-	Load	l per	tyre	in kç)		
3.20	Index	Symbols	14111	(kg)	(kPa)	(mm)	(mm)	(mm)	kPa	60	80	100	120	140	160	200	240	280	320	360	400
500/70R24 IND	164/164	A8/B	DW16LDW15L	5000	400	1302	511	28.0	0km/h 10km/h 30km/h 40km/h 50km/h	2625 1870 1750	3075 2190 2050	3525 2515 2350	3975 2835 2650	4425 3155 2950	4800 3420 3200 3200	5325 3795 3550 3550	5625 4010 3750 3750	6150 4385 4100 4100	4760 4450 4450	7125 5080 4750 4750	7500 5350 5000 5000
400/70R18 IND	147/147	A8/B	13.00	3075	400	1017	404	23.0	0km/h 10km/h 30km/h 40km/h 50km/h							2535 1980 1850 1850	2720 2125 1985 1985	3075 2400 2245 2245	5260 3430 2680 2505 2505	3825 2985 2790 2790	4215 3290 3075 3075
400/70R20 IND	149/149	A8/B	13.00	3250	400	1068	404	23.0	0km/h 10km/h 30km/h 40km/h							2545 2115 1960	2760 2265 2100	3180 2570 2375	5530 3605 2870 2650	4030 3175 2950	4455 3480 3250



LR400 Radial Agricultural Tire

- Increase traction performance.
 Enhance shoulder wear and cut resistance performance.
 Suitable for loaders and backhoe loaders.

Size	Load	Speed	Rim	Max.Load	Inflated Pressure	Overall Diameter	Section Width	Tread Depth	r ressure(iii a) Edda per tyre ii riig												
	Index	Symbols		(kg)	(kPa)	(mm)	(mm)	(mm)	kPa	60	80	100									
405/70R18	141/153	B/A2	13	2575	380	1025	407	23.0	0km/h 10km/h 30km/h 40km/h 50km/h			1605 1285 1160 1130	1755 1405 1270 1235	1900 1515 1375 1335	2050 1635 1480 1440	2340 1530 1690 1645	2630 2105 1905 1850	2930 2340 2120 2060	5445 3400 2715 2460 2390	3515 2810 2540 2470	3665 2930 2650 2575
405/70R20	143/155	B/A2	13	2725	380	1076	407	23.0	0km/h 10km/h 30km/h 40km/h 50km/h			1360	1855 1485 1340	2010 1610 1450	2165 1735 1565	2480 1980 1790	2790 2230 2020	3100 2480 2245	3415 2725 2470	3725 2975 2695	3880 3100 2810





Loader

E-3/L-3 **OTR Tire**

1. Available for large self-dumping trucks. 2.Wear resistance, good grip and self-cleaning performance.

C:	DI D .:	0.	10k	m/h	50	km/h	Section	Overall	Tread	_
Size	Ply Rating	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)	Width (mm)	Diameter (mm)	Depth (mm)	Type
29.5-29	28	25.00/3.5	19000	425	12150	325	750	1975	40.0	TL





C:			10k	m/h	50k	m/h	Section	Overall	Tread	_
Size	Ply Rating	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)	Width (mm)	Diameter (mm)	Depth (mm)	Туре
15.5-25	12	12.00/1.3	5600	400	3250	250	395	1275	25.0	TL
17.5-25	12	14.00/15	6150	350	3650	225	445	1350	25.5	TT/TL
17.5-25	16	14.00/15	7300	475	4250	300	445	1350	25.5	TT/TL
20.5-25	16	17.00/2.0	8250	350	5450	275	520	1490	28.5	TT/TL
20.5-25	20	17.00/2.0	9500	450	6000	325	520	1490	28.5	TT/TL
23.5-25	16	19.50/2.5	9500	300	6150	225	595	1615	31.5	TT/TL
23.5-25	18	19.50/2.5	10500	350	6700	275	595	1615	31.5	TT
23.5-25	20	19.50/2.5	10900	375	7300	300	595	1615	31.5	TT/TL
23.5-25	24	19.50/2.5	12500	475	8000	350	595	1615	31.5	TT
26.5-25	20	22.00/3.0	13200	350	8250	250	675	1750	35.0	TT
26.5-25	24	22.00/3.0	14000	400	9250	300	675	1750	35.0	TL
26.5-25	28	22.00/3.0	15500	475	10000	350	675	1750	35.0	TT/TL
29.5-25	28	25.00/3.5	17500	425	11500	325	750	1875	40.0	TL



Dump Truck



1. Available for large rigid dump trucks.
2. Wear resistance, good grip and self-cleaning
performance.

Size	Ply Rating	a Rim	10k	m/h	50k	m/h	Section	Overall	Tread	_
Size	Ply Rating	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)	(mm)	Diameter (mm)	Depth (mm)	Туре
16.00-25	28	11.25/2.0	11500	750	6700	575	430	1495	28.5	TT/TL
16.00-25	32	11.25/2.0	12500	875	7300	650	430	1495	28.5	TT/TL
16.00-25	36	11.25/2.0	13600	975	7750	725	430	1495	28.5	TT





1. Available for large self-dumping trucks. 2.Wear resistance, good grip and self-cleaning performance.

C:	DI D .:	6.	10k	m/h	50k	km/h	Section	Overall	Tread	_
Size	Ply Rating	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)	Width (mm)	Diameter (mm)	Depth (mm)	Туре
18.00-25	32	13.00/2.5	15000	750	8750	575	500	1615	30.0	TT/TL
18.00-25	40	13.00/2.5	17000	950	9750	700	500	1615	30.0	TT/TL





1. Available for large self-dumping trucks. 2.Wear resistance, good grip and self-cleaning performance.

C:	al a		10k	m/h	50k	km/h	Section	Overall	Tread	
Size	Ply Rating	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)	Width (mm)	Diameter (mm)	Depth (mm)	Туре
18.00-25	32	13.00/2.5	15000	750	8750	575	500	1615	30.0	TT
18.00-25	36	13.00/2.5	16000	850	9250	625	500	1615	30.0	TT





- 1. Available for large rigid dump trucks.
- 2. Wear resistance, good grip and self-cleaning performance.

C:	D	o:	10k	m/h	50k	m/h	Section	Overall	Tread	_
Size	Ply Rating	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)	Width (mm)	Diameter (mm)	Depth (mm)	Туре
14.00-24	28	10.0	10000	925	5600	650	375	1370	27	TT
14.00-25	36	10.00/1.5	11050	1100	5500	850	375	1370	27	TT





- 1. Available for large rigid dump trucks.
- 2. Wear resistance, good grip and self-cleaning performance.

Size	DI D .:	S.	10k	m/h	50k	m/h	Section	Overall	Tread	_
Size	Ply Rating	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)	Width (mm)	Diameter (mm)	Depth (mm)	Туре
18.00-33	32	13.00	17500	750	10000	575	500	1875	50.0	TL
18.00-33	36	13.00	18500	850	10600	625	500	1875	50.0	TL
18.00-33	40	13.00	19500	950	11200	700	500	1875	50.0	TL



Graders

E-2/L-2OTR Tire

1.Good steer and traction.
 2.Off-road pattern has self-cleaning performance and comfort.

C:	0 0	6:	10k	m/h	50k	km/h	Section	Overall	Tread	_
Size	Ply Rating	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)	Width (mm)	Diameter (mm)	Depth (mm)	Туре
15.5-25	12	12.00/1.3	5600	400	3250	250	395	1275	24.0	TL
17.5-25	12	14.00/1.5	6150	350	3650	225	445	1350	25.5	TT/TL
17.5-25	16	14.00/1.5	7300	475	4250	300	445	1350	25.5	TT/TL
20.5-25	16	17.00/2.0	8250	350	5450	275	520	1490	28.5	TT/TL
20.5-25	20	17.00/2.0	9500	450	6000	325	520	1490	28.5	TT/TL
23.5-25	16	19.50/2.5	9500	300	6150	225	595	1615	31.5	TT/TL
23.5-25	20	19.50/2.5	10900	375	7300	300	595	1615	31.5	TT/TL
23.5-25	24	19.50/2.5	12500	475	8000	350	595	1615	31.5	TT



G-2
OTR Tire

1.Good steer and traction.
2.Off-road pattern has self-cleaning performance and comfort.

C:	D 0	Ply Rating Rim	10km/h		40km/h		Section	Overall	Tread	_
Size	Ply Rating	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)	Width (mm)	Diameter (mm)	Depth (mm)	Туре
13.00-24	12	8.00TG	5600	450	2725	300	335	1280	24.0	TL
13.00-24	18	8.00TG	6700	675	3500	450	335	1280	24.0	TL
14.00-24	12	8.00TG	6300	425	3075	275	360	1350	24.0	TT/TL
14.00-24	16	8.00TG	7300	550	3650	350	360	1350	24.0	TT/TL





LMS401 OTR Tire

Radial OTR

Exceptional traction

Massive tread blocks characterise this tyre, it delivers excellent tractive performance, better lateral adhesion and more efficient loading for machines working at the face.

Dump Truck

Good self cleaning

Flower chimb angle changed design, it delivers good self cleaning.

Operating comfort

A wide, square tread gives better stability in loading operations and whilst travelling.

Size		Load	Index			LOAD C	APACITY				
		TRANSP	LOADING		TRAN	SPORT	LOAD	ING	Overall	Section	Tread
	Ply Rating	50km/h Speed Symbol B	10km/h Speed Symbol A2	Rim	LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)	Diameter (mm)	Width (mm)	Depth (mm)
23.5R25	₩	185	201	19.5/2.5	9250	475	14500	600	1673	597	50.5
26.5R25	₩	193	209	22.00/3.0	11500	475	18500	600	1798	673	55.5
29.5R25	₩	200	216	25.00/3.5	14000	475	22400	600	1921	750	60.5



DO993OTR Tire

- 1.Good traction resistance.
- 2. Chip, cut and abrasion resistance tread compound.
- 3.Deep tread depth increases mileage and service life.

		Load	Index			LOAD CA	APACITY				
<u>.</u>		TRANSP	LOADING		TRANS	SPORT	LOAD	ING	Overall	Section	Tread
3120	Ply Rating	50km/h Speed Symbol B	10km/h Speed Symbol A2	Rim	LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)	Diameter (mm)	Width (mm)	Depth (mm)
13.00R25	###	163	182	8.50	4875	700	8500	950	1300	350	30.0
14.00R24	####	169	188	10.00	5800	700	10000	950	1370	375	30.0
14.00R25	***	169	188	10.00	5800	700	10000	950	1370	375	30.0
▲ 13.00R25	\$\$\$	163	182	10.00	4875	700	8500	950	1300	350	28.0
▲ 14.00R24	***	169	188	10.00	5800	700	10000	950	1370	375	28.0
▲ 14.00R25	####	169	188	10.00	5800	700	10000	950	1370	375	28.0

attention: ▲ indicates information for DO993+



LB02S OTR Tire

- 1.Exceptional traction and manoeuvreability.
- 2.Good flotation.
- 3.Excellent stability and comfort.

			Load	Index			LOAD C	APACITY				
	Size		TRANSP	LOADING		TRAN:	SPORT	LOAD	ING	Overall	Section	Tread
		Ply Rating	50km/h Speed Symbol B	10km/h Speed Symbol A2	Rim	LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)	Diameter (mm)	Width (mm)	Depth (mm)
	18.00R33	☆☆	191	209	13.00/2.5	10900	650	18500	800	1877	498	53.0





- 1.Self-cleaning tread design provides good traction and stability on the soft and muddy ground.
- 2.Tire side anti-friction design , prevent tire side scratch damage.
- 3.Deepened tread provides excellent wear resistance.

		Load	Index			LOAD C	APACITY				
c.		TRANSP	LOADING		TRAN:	SPORT	LOAD	ING	Overall	Section	Tread
Size	Ply Rating	50km/h Speed Symbol B	10km/h Speed Symbol A2	Rim	LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)	Diameter (mm)	Width (mm)	Depth (mm)
16.00R25	☆☆	177	195	11.25/2.0	7300	650	12150	800	1548	432	42.0
18.00R25	☆☆	185	204	13.00/2.5	9250	650	16000	800	1673	498	46.0





1.Good traction and wear resistance.
2.Excellent tear resistance.

Size		Load	Index			LOAD C	APACITY				
		TRANSP	LOADING		TRAN	SPORT	LOAD	ING	Overall	Section	Tread
	Ply Rating	50km/h Speed Symbol B	10km/h Speed Symbol A2	Rim	LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)	Diameter (mm)	Width (mm)	Depth (mm)
750/65R25	**	190	209	24.00/3.0	10600	475	18500	625	1610	754	43.5
26.5R25	22	193	209	22.00/3.0	11500	475	18500	600	1750	673	42.5
29.5R25	**	200	216	25.00/3.5	14000	475	22400	600	1873	750	42.5





1.Long life.

2.Excellent adhension and traction in bad conditions.

		Load	Index			LOAD C	APACITY				
Size		TRANSP	LOADING		TRAN:	SPORT	LOAD	ING	Overall	Section	Tread
	Ply Rating	50km/h Speed Symbol B	10km/h Speed Symbol A2	Rim	LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)	Diameter (mm)	Width (mm)	Depth (mm)
14.00R25	\$\$\$	169	188	10.00	5800	700	10000	950	1370	375	24.0



DM992+OTR Tire

- 1.Long life.
- 2.Excellent adhension and traction in bad conditions.

		Load	Index			LOAD C	APACITY				
.		TRANSP	LOADING		TRAN:	SPORT	LOAD	ING	Overall	Section	Tread
Size	Ply Rating	50km/h Speed Symbol B	10km/h Speed Symbol A2	Rim	LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)	Diameter (mm)	Width (mm)	Depth (mm)
13.00R25	***	163	182	10.00	4875	700	8500	950	1300	350	26.0
14.00R24	***	169	188	10.00	5800	700	10000	950	1370	375	26.0



Loader

LB01N OTR Tire

- 1.Exceptional traction and manoeuvreability.
- 2.Good flotation.
- 3.Excellent stability and comfort.

		Load	Index			LOAD C	APACITY				
~ :		TRANSP	LOADING		TRANS	SPORT	LOAD	ING	Overall	Section	Tread
Size	Ply Rating	50km/h Speed Symbol B	10km/h Speed Symbol A2	Rim	LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)	Diameter (mm)	Width (mm)	Depth (mm)
17.5R25	☆☆	167	182	14.00/1.5	5450	475	8500	600	1348	445	27.0
20.5R25	☆☆	177	193	17.00/2.0	7300	475	11500	600	1492	520	30.0
23.5R25	☆☆	185	201	19.5/2.5	9250	475	14500	600	1617	597	33.0
26.5R25	☆☆	193	209	22.00/3.0	11500	475	18500	600	1750	673	36.0
29.5R25	☆☆	200	216	25.00/3.5	14000	475	22400	600	1873	750	39.0



LM01N OTR Tire

1.Exceptional traction and manoeuvreability.

2.Good flotation.

3.Excellent stability and comfort.

	Size		Load	Index			LOAD C	APACITY				
			TRANSP	LOADING		TRAN:	SPORT	LOAD	ING	Overall	Section	Tread
		Ply Rating	50km/h Speed Symbol B	10km/h Speed Symbol A2	Rim	LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)	Diameter (mm)	Width (mm)	Depth (mm)
l	23.5R25	₩	185	201	19.5/2.5	9250	475	14500	600	1617	597	30.5



LB03SD OTR Tire

Exceptionally robust in masacre conditions

A substantial crown, robust shoulders reinforced with a protection band make up a tyre particularly resistant to shock ruptures, cuts and tread tearing.

A particularly resilient casing with the addition of several specific steel belts constitute a tyre that is very resistant to punctures.

Excellent compromise of adhesion and traction

A very substantial, wide and aggressive tread functions perfectly to produce a good compromise between adhesion, traction and damage resistance.

		Load	Index			LOAD C	APACITY				
c.		TRANSP	LOADING		TRANS	SPORT	LOAD	ING	Overall	Section	Tread
	Ply Rating	50km/h Speed Symbol B	10km/h Speed Symbol A2	Rim	LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)	Diameter (mm)	Width (mm)	Depth (mm)
17.5R25	₩	167	182	14.00/1.5	5450	475	8500	600	1399	445	62.5
20.5R25	₩	177	193	17.00/2.0	7300	475	11500	600	1548	520	70.0
23.5R25	₩	185	201	19.5/2.5	9250	475	14500	600	1673	597	76.0
26.5R25	₩	193	209	22.00/3.0	11500	475	18500	600	1798	673	85.0
29.5R25	☆☆	200	216	25.00/3.5	14000	475	22400	600	1921	750	92.5



LB02SD OTR Tire Exceptional traction

Massive tread blocks characterise this tyre;

High Efficiency

The extra deep tread pattern (L5) of this tyre gives outstanding wear life potential
The sidewall/tread intersection design gives an excellent level of damage and cut resistance

Operating comfort

A wide, square tread gives better stability in loading operations and whilst travelling A directional pattern

	-	Load	Index			LOAD C	APACITY				
		TRANSP	LOADING		TRAN:	SPORT	LOAD	ING	Overall	Section	Tread
	Ply Rating	50km/h Speed Symbol B	10km/h Speed Symbol A2	Rim	LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)	Diameter (mm)	Width (mm)	Depth (mm)
20.5R25	\$\$	177	193	17.00/2.0	7300	475	11500	600	1548	520	70.0
23.5R25	₩	185	201	19.5/2.5	9250	475	14500	600	1673	597	76.0
26.5R25	☆☆	193	209	22.00/3.0	11500	475	18500	600	1798	673	85.0
29.5R25	₩	200	216	25.00/3.5	14000	475	22400	600	1921	750	92.5





- 1. Good traction and wear resistance.
- 2.Excellent tear resistance.

	ļ.	Load	Index			LOAD C	APACITY				
C :		TRANSP	LOADING		TRAN:	SPORT	LOAD	ING	Overall	Section	Tread
Size	Ply Rating	50km/h Speed Symbol B	10km/h Speed Symbol A2	Rim	LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)	Diameter (mm)	Width (mm)	Depth (mm)
850/65R25	**	196	207	27.00/3.5	12500	475	17500	625	1740	850	44.5
750/65R25	☆☆	190	209	24.00/3.0	10600	475	18500	625	1610	754	43.5



LD702 OTR Tire

Sand

1. The combination of vertical and horizontal pattern groove. 2. Strengthened bead area and Tubeless solution preventing sudden pressure loss.

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
24R20.5	☆/16PR	176	F	18.00	7100	600	1370	600	22.0





- **Mobile Crane**
- 1. Exceptional traction and manoeuvreability.
- 2.Good flotation.
- 3.Excellent stability and comfort.

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
445/95R25	☆☆	177	E	11.25/2.0	7300	900	1481	435	23.0
385/95R25	\$\$	170	E	10.00/1.5	6000	900	1369	379	21.0



LSN201

SNOW WORKS

- 1.Good traction resistance.
- 2.Chip,cut and abrasion resistance tread compound.
- 3.Suitable for snow work.

	Ply Rating	Load Index			LOAD CAPACITY						
c.		TRANSP	LOADING	Rim	TRANSPORT		LOADING		Overall	Section	Tread
Size		50km/h Speed Symbol B	10km/h Speed Symbol A2		LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)	Diameter (mm)	Width (mm)	Depth (mm)
15.525	☆☆	160	176	12.00/1.3	4500	475	7100	600	1277	394	25.0
17.525	☆☆	167	182	14.00/1.5	5450	475	8500	600	1348	445	28.0
20.525	☆☆	177	193	17.00/2.0	7300	475	11500	600	1492	520	32.0
23.525	☆☆	185	201	19.50/2.5	9250	475	14500	600	1617	597	33.0
26.525	☆☆	193	209	22.00/3.0	11500	475	18500	600	1750	673	36.0