



The world at your reach.

L-T10

- Center ribs stiffeners with hidden grooves for wear and cornering performance.
- Edge blades to prevent groove edge river wear.
- Blades variable depth for optimum rib flexion, uniform wear and wet braking performance.



Long Haul

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load andInflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					(Dual-kg)	(Dual-kpa)	(Single-kg)	(Single-kpa)				
385/55R19.5	156	156	J	18	--	--	4000	900	919	386	12.5	ETRTO
435/50R19.5	160	160	J	20	--	--	4500	900	931	438	12.5	ETRTO
445/45R19.5	160	160	J	20	--	--	4500	900	895	446	12.5	ETRTO

L-S20

- Suitable for medium trucks running on the high-grade road.
- Stone rejection design protect groove bottom from stone puncture.
- Safe driving and braking thanks to 4 Z-shaped longitudinal grooves.



Light Truck

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load andInflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					(Dual-kg)	(Dual-kpa)	(Single-kg)	(Single-kpa)				
205/75R17.5	14	124/122	M	6.00	1500	750	1600	750	753	204	10.5	ETRTO
215/75R17.5	14	126/124	M	6.00	1600	700	1700	700	767	211	11.5	ETRTO
215/75R17.5	16	135/133	J	6.00	2060	850	2180	850	767	211	11.5	ETRTO
225/75R17.5	12	126/125	M	6.75	1650	675	1700	675	783	226	11.5	ETRTO
225/75R17.5	14	129/127	M	6.75	1750	725	1850	725	783	226	11.5	ETRTO
235/75R17.5	14	132/130	M	6.75	1900	775	2000	775	797	233	12.5	ETRTO
235/75R17.5	16	141/140	J	6.75	2500	850	2575	850	797	233	12.5	ETRTO
235/75R17.5	18	143/141	J	6.75	2575	875	2725	875	797	233	12.5	ETRTO
245/70R17.5	14	134/132	M	7.50	2000	775	2120	775	789	248	12.5	ETRTO
245/70R17.5	16	136/134	M	7.50	2120	850	2240	850	789	248	12.5	ETRTO
245/70R17.5	18	143/141	J	7.50	2575	900	2725	900	789	248	12.5	ETRTO
245/70R19.5	14	133/131	M	7.50	1950	750	2060	750	839	248	12.5	ETRTO
245/70R19.5	16	136/134	M	7.50	2120	825	2240	825	839	248	12.5	ETRTO
245/70R19.5	18	141/140	J	7.50	2500	850	2575	850	839	248	12.5	ETRTO

L-D20

- Suitable for medium trucks running on the high-grade road.
- New siping design improves wet performance.
- Low rolling resistance, reducing fuel consumption.



Light Truck

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load andInflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					(Dual-kg)	(Dual-kpa)	(Single-kg)	(Single-kpa)				
205/75R17.5	14	124/122	M	6.00	1500	750	1600	750	753	204	11.5	ETRTO
215/75R17.5	14	126/124	M	6.00	1600	700	1700	700	767	211	12.5	ETRTO
225/75R17.5	12	126/125	M	6.75	1650	675	1700	675	783	226	12.5	ETRTO
225/75R17.5	14	129/127	M	6.75	1750	725	1850	725	783	226	12.5	ETRTO
235/75R17.5	14	132/130	M	6.75	1900	775	2000	775	797	233	13.5	ETRTO
245/70R17.5	14	134/132	M	7.50	2000	775	2120	775	789	248	14.5	ETRTO
245/70R17.5	16	136/134	M	7.50	2120	850	2240	850	789	248	14.5	ETRTO
245/70R19.5	14	133/131	M	7.50	1950	750	2060	750	839	248	14.5	ETRTO
245/70R19.5	16	136/134	M	7.50	2120	825	2240	825	839	248	14.5	ETRTO

L-T20

- Suitable for medium trucks running on the high-grade road.
- New siping design improves wet performance.
- Low rolling resistance, reducing fuel consumption.



Light Truck

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load andInflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					(Dual-kg)	(Dual-kpa)	(Single-kg)	(Single-kpa)				
205/65R17.5	16	129/127(132/132)	J(G)	6.00	1750	900	1850	900	711	204	12.5	ETRTO
215/75R17.5	16	135/133	J	6.00	2060	850	2180	850	767	211	12.5	ETRTO
235/75R17.5	16	141/140	J	6.75	2500	850	2575	850	797	233	12.5	ETRTO
235/75R17.5	18	143/141	J	6.75	2575	875	2725	875	797	233	12.5	ETRTO
235/75R17.5	18	143/141(145/145)	J(F)	6.75	2575	875	2725	875	797	233	12.5	ETRTO
245/70R17.5	18	143/141	J	7.50	2575	900	2725	900	789	248	12.5	ETRTO
245/70R17.5	18	143/141(146/146)	J(F)	7.50	2575	900	2725	900	789	248	12.5	ETRTO

W-D60

- Suitable for drive axle of trucks under snow condition.
- Lasting grip and stability ,with 3PMSF marking.
- Optimized rib contact combats uneven wear and improves wet handling and braking.



Winter

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load andInflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					(Dual-kg)	(Dual-kpa)	(Single-kg)	(Single-kpa)				
295/80R22.5	18	154/149	M	9.00	3250	850	3750	850	1044	298	18.5	ETRTO
315/70R22.5	18	156/150(154/150)	L(M)	9.00	3350	900	4000	900	1014	312	20.0	ETRTO
315/80R22.5	22	158/150(154/150)	L(M)	9.00	3350	900	4250	900	1076	312	20.0	ETRTO

W-S60

- Suitable for steer and trailer axle of trucks under snow condition.
- Deeper and higher density of lateral grooves and sipes for better grip.
- Zig-Zag grooves design provides excellent traction on icy and wet road condition.



Winter

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load andInflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					(Dual-kg)	(Dual-kpa)	(Single-kg)	(Single-kpa)				
295/80R22.5	18	154/149	M	9.00	3250	850	3750	850	1044	298	15.5	ETRTO
315/70R22.5	16	154/150(152/148)	L(M)	9.00	3350	900	3750	900	1014	312	15.5	ETRTO
315/70R22.5	18	156/150(154/150)	L(M)	9.00	3350	900	4000	900	1014	312	15.5	ETRTO
315/80R22.5	22	158/150(154/150)	L(M)	9.00	3350	900	4250	900	1076	312	15.5	ETRTO
385/55R22.5	20	160(158)	K(L)	12.25	--	--	4500	900	996	386	13.5	ETRTO
385/65R22.5	24	164(158)	K(L)	11.75	--	--	5000	900	1072	389	15.5	ETRTO

LINGLONG HIGH-END PRODUCTS OF TRUCKS TIRES

PRODUCT MANUALS 2023

R-S30

- Blades variable depth for optimum rib flexion, uniform wear and wet braking performance.
- Slightly directional design to provide grip in forward & braking direction.
- Groove stone ejectors help prevent stone trapping and drilling to enhance casing toughness and retreadability.



Regional

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load andInflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					(Dual-kg)	(Dual-kpa)	(Single-kg)	(Single-kpa)				
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	15.5	ETRTO
295/80R22.5	18	154/149	M	9.00	3250	850	3750	850	1044	298	15.5	ETRTO
315/70R22.5	16	154/150(152/148)	L(M)	9.00	3350	900	3750	900	1014	312	15.5	ETRTO
315/70R22.5	18	156/150(154/150)	L(M)	9.00	3350	900	4000	900	1014	312	15.5	ETRTO
315/80R22.5	20	156/150(154/150)	L(M)	9.00	3350	850	4000	850	1076	312	15.5	ETRTO
315/80R22.5	22	158/150(154/150)	L(M)	9.00	3350	900	4250	900	1076	312	15.5	ETRTO
385/55R22.5	18	158	L	12.25	--	--	4250	850	996	386	13.5	ETRTO
385/55R22.5	20	160	K(L)	12.25	--	--	4500	900	996	386	13.5	ETRTO
385/65R22.5	20	160	K(L)	11.75	--	--	4500	900	1072	389	15.5	ETRTO
385/65R22.5	24	164	K(L)	11.75	--	--	5000	900	1072	389	15.5	ETRTO

R-T30

- New sipes Improve grip and resistance to tread tearing in severe conditions of use.
- New groove shapes provides greater traction on slippery road surfaces.



Regional

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load andInflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					(Dual-kg)	(Dual-kpa)	(Single-kg)	(Single-kpa)				
385/55R22.5	18	158	L	12.25	--	--	4250	850	996	386	13.5	ETRTO
385/55R22.5	20	160(158)	K(L)	12.25	--	--	4500	900	996	386	13.5	ETRTO
385/65R22.5	20	160(158)	J(L)	11.75	--	--	4500	900	1072	389	13.5	ETRTO
385/65R22.5	24	164	J	11.75	--	--	5000	900	1072	389	13.5	ETRTO
425/65R22.5	20	165	J	12.25	--	--	5150	825	1124	422	14.0	ETRTO

R-D30

- New sipes Improve grip and resistance to tread tearing in severe conditions of use.
- New groove shapes provides greater traction on slippery road surfaces.



Regional

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load andInflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					(Dual-kg)	(Dual-kpa)	(Single-kg)	(Single-kpa)				
295/60R22.5	16	150/147	L	9.00	3075	900	3350	900	926	292	18.0	ETRTO
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	20.5	ETRTO
295/80R22.5	18	154/149	L	9.00	3250	850	3750	850	1044	298	20.5	ETRTO
315/60R22.5	16	152/148	L	9.75	3150	900	3550	900	950	313	19.5	ETRTO
315/70R22.5	16	154/150(152/148)	L(M)	9.00	3350	900	3750	900	1014	312	20.0	ETRTO
315/70R22.5	18	156/150(154/150)	L(M)	9.00	3350	900	4000	900	1014	312	20.0	ETRTO
315/80R22.5	18	154/150	M	9.00	3350	825	3750	825	1076	312	22.0	ETRTO
315/80R22.5	20	156/150(154/150)	L(M)	9.00	3350	850	4000	850	1076	312	22.0	ETRTO

L-S20

- Safe driving and braking thanks to 4 Z-shaped longitudinal grooves.
- Suitable for medium trucks running on the high-grade road.
- Stone rejection design protect groove bottom from stone puncture.



Regional

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load andInflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					(Dual-kg)	(Dual-kpa)	(Single-kg)	(Single-kpa)				
265/70R17.5	16	140/138	M	7.50	2360	800	2500	800	817	262	13.5	ETRTO
265/70R17.5	18	145/143	J	7.50	2725	900	2900	900	817	262	13.5	ETRTO
265/70R19.5	14	136/134	M	7.50	2120	725	2240	725	867	262	13.5	ETRTO
265/70R19.5	16	140/138	M	7.50	2360	775	2500	775	867	262	13.5	ETRTO
265/70R19.5	18	143/141	J	7.50	2575	850	2725	850	867	262	13.5	ETRTO
285/70R19.5	18	146/144	M	8.25	2800	900	3000	900	895	283	12.0	ETRTO
285/70R19.5	18	150/148	J	8.25	3150	900	3350	900	895	283	12.0	ETRTO
305/70R19.5	18	148/145	M	9.00(8.25)	3150	850	2900	850	923	305	13.5	ETRTO

L-D20

- Suitable for medium trucks running on the high-grade road.
- New siping design improves wet performance.
- Low rolling resistance, reducing fuel consumption.



Regional

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load andInflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					(Dual-kg)	(Dual-kpa)	(Single-kg)	(Single-kpa)				
265/70R17.5	16	140/138	M	7.50	2360	800	2500	800	817	262	15.5	ETRTO
265/70R19.5	14	136/134	M	7.50	2120	725	2240	725	867	262	15.5	ETRTO
265/70R19.5	16	140/138	M	7.50	2360	775	2500	775	867	262	15.5	ETRTO
285/70R19.5	18	146/144	M	8.25	2800	900	3000	900	895	283	13.5	ETRTO
305/70R19.5	18	148/145	M	9.00(8.25)	3150	850	2900	850	923	305	13.5	ETRTO

M-A40

- Tread Compound helps resist cuts and chips for enhanced retreadability.
- Groove stone ejectors help prevent stone trapping and drilling to enhance casing toughness and retreadability.
- All-position tread design helps enhance traction on and off the road.



On&Off Road

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load andInflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					(Dual-kg)	(Dual-kpa)	(Single-kg)	(Single-kpa)				
13R22.5	18	156/150	K	9.75	3350	875	4000	875	1124	320	18.0	ETRTO
13R22.5	20	158/156	K	9.75	4000	900	4250	900	1124	320	18.0	ETRTO
315/80R22.5	20	156/150	K	9.00	3350	850	4000	850	1076	312	19.0	ETRTO
315/80R22.5	22	158/150	K	9.00	3350	900	4250	900	1076	312	19.0	ETRTO
385/65R22.5	20	160(158)	K(L)	11.75	--	--	4500	900	1072	389	18.0	ETRTO

M-D41

- Robust tread pattern and high traction on rough surfaces.
- High resistance to cutting and chipping.
- New tread compound improved resistance to wear and tear.



On&Off Road

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load andInflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					(Dual-kg)	(Dual-kpa)	(Single-kg)	(Single-kpa)				
13R22.5	18	156/150	K	9.75	3350	875	4000	875	1124	320	21.0	ETRTO
13R22.5	20	158/156	K	9.75	4000	900	4250	900	1124	320	21.0	ETRTO
315/80R22.5	22	158/150	K	9.00	3350	900	4250	900	1076	312	21.0	ETRTO
315/80R22.5	20	156/150	K	9.00	3350	850	4000	850	1076	312	21.0	ETRTO

F-A01

- Suitable for mixed use trailer service in on/off road applications.
- High resistance to cutting and chipping.
- New tread compound improved resistance to wear and tear.



On&Off Road

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load andInflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					(Dual-kg)	(Dual-kpa)	(Single-kg)	(Single-kpa)				
235/75R17.5	18	143/141	J	6.75	2575	875	2725	875	797	233	13.0	ETRTO
265/70R19.5	18	143/141	J	7.50	2575	850	2725	850	867	262	17.5	ETRTO
275/70R22.5	16	148/145	J/M	8.25	2900	900	3150	900	958	276	15.0	ETRTO
285/70R19.5	20	150/148	J	8.25	3150	900	3350	850	895	283	14.0	ETRTO

M-D40

- Progressive, variable-width grooves, less stone retention.
- New groove shapes provides greater traction on slippery road surfaces.
- New tread compound improved resistance to wear and tear.



On&Off Road

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load andInflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					(Dual-kg)	(Dual-kpa)	(Single-kg)	(Single-kpa)				
13R22.5	18	156/150	K	9.75	3350	875	4000	875	1124	320	21.0	ETRTO
13R22.5	20	158/156	K	9.75	4000	900	4250	900	1124	320	21.0	ETRTO
315/80R22.5	22	158/150	K	9.00	3350	900	4250	900	1076	312	21.0	ETRTO
315/80R22.5	20	156/150	K	9.00	3350	850	4000	850	1076	312	21.0	ETRTO

